



RB Series POLYIMIDE LEVELING FEET

VibraSystems **RB** series adjustable levelers utilize the latest developments in the engineering and manufacturing of extra strong, durable, reinforced Polyimide Nylon construction materials. These mounts have excellent load bearing capacity and can be used for light, medium and heavy duty applications. Swivel stem compensate for uneven floors and are available in zinc plated or stainless steel. Rubber anti-vibration pads are available for all styles of **RB** levelers to provide a non-slip contact with the floor. The nylon base is corrosion resistant and good for regular wash-down procedures as employed in the food, chemical and pharmaceutical industries.



| Part Number | Base Material | Base Diameter (ins) | Stud Length (ins) | Overall Height (ins) | Stem Thread | Stem Material | Load per Mount (lbs) |
|-------------|------------------------------|---------------------|-------------------|----------------------|-------------|---------------|----------------------|
| RB110-3-S | Reinforced Polyamide (Nylon) | 2 | 3-1/8 | 3-3/4 | 3/8-16 | Stainless | 700 |
| RB110-3-P | | 2 | 3-1/8 | 3-3/4 | 3/8-16 | Zinc Plated | |
| RB110-4-S | | 2 | 3-1/8 | 3-3/4 | 1/2-13 | Stainless | |
| RB110-4-P | | 2 | 3-1/8 | 3-3/4 | 1/2-13 | Zinc Plated | |
| Part Number | Base Material | Base Diameter (ins) | Stud Length (ins) | Overall Height (ins) | Stem Thread | Stem Material | Load per Mount (lbs) |
| RB120-3-S | Reinforced Polyamide (Nylon) | 1-9/16 | 3-1/16 | 4 | 3/8-16 | Stainless | 2200 |
| RB120-3-P | | 1-9/16 | 3-1/16 | 4 | 3/8-16 | Zinc Plated | |
| RB120-4-S | | 1-9/16 | 3-1/16 | 4 | 1/2-13 | Stainless | |
| RB120-4-P | | 1-9/16 | 3-1/16 | 4 | 1/2-13 | Zinc Plated | |
| Part Number | Base Material | Base Diameter (ins) | Stud Length (ins) | Overall Height (ins) | Stem Thread | Stem Material | Load per Mount (lbs) |
| RB130-4-S | Reinforced Polyamide (Nylon) | 3-1/8 | 5-3/8 | 6 | 1/2-13 | Stainless | 2200 |
| RB130-4-P | | 3-1/8 | 5-3/8 | 6 | 1/2-13 | Zinc Plated | |
| RB130-5-S | | 3-1/8 | 5-3/8 | 6 | 5/8-11 | Stainless | |
| RB130-5-P | | 3-1/8 | 5-3/8 | 6 | 5/8-11 | Zinc Plated | |
| Part Number | Base Material | Base Diameter (ins) | Stud Length (ins) | Overall Height (ins) | Stem Thread | Stem Material | Load per Mount (lbs) |
| RB140-5-S | Reinforced Polyamide (Nylon) | 4 | 5-5/8 | 7-1/2 | 5/8-11 | Stainless | 2200 |
| RB140-5-P | | 4 | 5-5/8 | 7-1/2 | 5/8-11 | Zinc Plated | |
| RB140-6-S | | 4 | 5-5/8 | 7-1/2 | 3/4-10 | Stainless | |
| RB140-6-P | | 4 | 5-5/8 | 7-1/2 | 3/4-10 | Zinc Plated | |
| Part Number | Base Material | Base Diameter (ins) | Stud Length (ins) | Overall Height (ins) | Stem Thread | Stem Material | Load per Mount (lbs) |
| RB150-6-S | Reinforced Polyamide (Nylon) | 5 | 5-7/16 | 8-1/4 | 3/4-10 | Stainless | 4500 |
| RB150-6-P | | 5 | 5-7/16 | 8-1/4 | 3/4-10 | Zinc Plated | |
| Part Number | Base Material | Base Diameter (ins) | Stud Length (ins) | Overall Height (ins) | Stem Thread | Stem Material | Load per Mount (lbs) |
| RB160-6-S | Reinforced Polyamide (Nylon) | 4-7/8 | 5-3/32 | 7-1/2 | 3/4-10 | Stainless | 10000 |
| RB160-6-P | | 4-7/8 | 5-3/32 | 7-1/2 | 3/4-10 | Zinc Plated | |
| RB160-8-S | | 4-7/8 | 5-3/32 | 7-1/2 | 1-8 | Stainless | |
| RB160-8-P | | 4-7/8 | 5-3/32 | 7-1/2 | 1-8 | Zinc Plated | |